



Heavy-Duty Performance

PREMIUM MATERIALS HANDLING PNEUMATIC

T-900

The T-900 pneumatic tyre was designed for heavy duty use on forklifts and other industrial equipment.

The T-900 has an excellent total value of ownership. Its reinforced sidewall, flat tread and special compounding provide for longer tyre life and extra resistance against side impacts. It's the preferred tyre of OEMs and a premium choice for today's aggressive applications.

PERFORMANCE DEFINED

TYRE LIFE

Trelleborg products guarantee **the best wear** performance in the industry. This results in longer tyre life, **additional hours of usage**, reduced downtime and lower maintenance costs.

ENERGY SAVING

Trelleborg is a **leading approved tyre manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption. This results in reduced fuel costs for our customers.

STABILITY

Trelleborg tyres are designed with **exceptional stability**. Our tyres are engineered to ensure **proper distribution of heat** and to prevent excessive deflection under load.

COMFORT

Trelleborg recognizes the importance of a **safe working environment**. Our products are designed to minimize vibration and **keep noise to a minimum level**. We follow the strictest regulations for work safety while providing a comfortable ride.

T-900

Tyre Size	Alternative Size	Ply Rating	Rim Size	Tyre Dimensions [mm]			Inflation Pressure [bar]	Tyre Type	Load Capacity [kg]	
				Overall Diameter	Section Width	Tread Depth			Forklift trucks up to 25 km/h	
									Load Wheel	Steering Wheel
5.00-8		10	3.00D-8	468	140	13	10	Tube Type	1415	1090
18x7-8	180/70-8	16	4.33R-8	462	168	16	10	Tube Type	2145	1650
6.00-9		12	4.00E-09	543	160	15	10	Tube Type	1885	1450
6.50-10		12	5.00F-10	590	182	18	9	Tube Type	2145	1650
23x9-10	225/75-10	20	6.50F-10	585	230	19	10	Tube Type	3445	2650
7.00-12		14	5.00S-12	680	191	18	9	Tube Type	2755	2120
7.00-12		16	5.00S-12	680	191	18	10	Tube Type	2910	2240
23x10-12	250/60-12	20	8.00G-12	600	245	22	10	Tube Type	3770	2900
27x10-12	250/75-12	16	8.00G-12	685	250	22	8	Tube Type	3900	3000
7.00-15	29x8-15	14	5.5-15	760	204	20	8.8	Tube Type	3275	2520
7.50-15		16	6.0-15	778	215	21	10	Tube Type	3900	3000
8.25-15		14	6.5-15	841	247	19	8	Tube Type	4225	3250
8.25-15		16	6.5-15	841	247	19	9.3	Tube Type	4615	3550
28x9-15	225/75-15 (8.15-15)	14	7.0-15	710	230	18	10	Tube Type	3900	3000
250-15	250/70-15	20	7.0-15	742	240	19	10	Tube Type	5040	3875
300-15	315/70-15	20	8.0-15	840	290	23	9	Tube Type	6500	5000
355/65-15	32x12½-15 (350-15)	24	9.75-15	843	334	29	10	Tube Type	7800	6000
355/65-15	32x12½-15 (350-15)	32	9.75-15	843	334	29	12.5	Tube Type	9490	7300
7.50-16	250/80-16	12	6.00G-16	805	220	21	8	Tube Type	3630	2790
9.00-20	270/95-20	14	7.0-20	1015	265	27	9	Tube Type	5850	4500
10.00-20	290/95-20	16	7.5-20	1085	294	32	9	Tube Type	6500	5000
11.00-20	300/95-20	18	8.0-20	1110	302	33	10	Tube Type	7800	6000
12.00-20	330/95-20	20	8.5-20	1145	325	35	10	Tube Type	9230	7100
12.00-20	330/95-20	24	8.5-20	1145	325	35	10.4	Tube Type	9710	7470
12.00-24	330/95-24	20	8.5-24	1245	320	35	10	Tube Type	9750	7500
12.00-24	330/95-24	24	8.5-24	1245	320	35	10.4	Tube Type	9945	7650
14.00-24	385/95-24	24	10.00W-24	1360	380	39	10	Tubeless	12350	9500
14.00-24	385/95-24	28	10.00W-24	1360	380	39	10.4	Tube Type	12600	9690

TREAD PATTERN



T-900

